## **TECHNICAL DATA SHEET**



## RED 'N' TACKY SPRAY GREASE

**PRODUCT # 11025** 

TEST	ASTM	TYPICAL
Thickener Type		Silica
Texture		Smooth & Tacky
Color		Red
Worked Penetration	D217	275 (after 60 strokes)
(with Propellant Removed)	5217	290 (after 10,000 strokes)
Timken OK Load, Lbs	D2509	60
Corrosion Prevention Test	D665	Pass
Base Oil Properties:		
Pour Point, °F	<b>D</b> 97	0
Flash Point, °F	<b>D92</b>	450
Base Oil Viscosity	<b>D445</b>	
@100°F, SUS		4,100
@210°F, SUS		280

Lucas Red "N" Tacky Spray Grease is a high-quality silica grease in a convenient aerosol package. The application is ideal for putting grease in those hard-to-reach areas. Our customers tell us there are many times that they'd prefer to lubricate a part or piece of equipment with grease, rather than a penetrating or general-purpose oil, common in aerosol cans, but need the convenience of a spray. Lucas Red "N" Tacky Spray Grease is the answer. Excellent for cars, trucks, RVs, industrial or farm equipment and around the house. Use wherever grease is the preferred lubricant.

## **Features:**

- A Narrow, Confined Spray Pattern
- Fast Carrier Solvent Evaporation
- Good Cling to the Applied Surface
- Resists Separation
- Resists Water Washout
- Good Heat Resistance
- Broad Temperature Use Range, 0°-450°F