## **TECHNICAL DATA SHEET**



## SxS TRANSMISSION FLUID

PRODUCT # 11216, 11217, 11218, 18050, 11219

TEST	ASTM	TYPICAL
API Gravity	D-1298	33.2
Specific Gravity @ 60°F	D-1298	0.859
Density @ 60°F LBS/US Gal	D-1298	7.17
Flash Point, PMCC °F	<b>D-93</b>	>400
Viscosity @ 40°C cSt	D-445	39.0
Viscosity @ 100°C cSt	D-445	8.0
Viscosity Index	D-2270	178
Color	Visual	Violet

**Lucas SxS Transmission Fluid** is blended from premium synthetic base oils only (API Groups III & V), combined with shear stable synthetic polymers, a high-quality additive package that includes anti-wear, anti-oxidants and corrosion inhibitors to produce a truly superior SxS transmission fluid. Lucas SxS Transmission Fluid was designed specifically to meet the requirements of Polaris vehicles' Transmissions/ Gearcase, including ACE, Sportsman, Ranger and RZR\* and may be used safely as a substitute for AGL.

**Lucas SxS Transmission Fluid** will not permanently shear thin, ensuring that viscosity remains constant over the life of the fluid. Synthetic SxS Transmission Fluid provides superior chain and gear wear protection. Reduces the effects of shock loading and will hold-up under heat and stress.

<sup>\*</sup>Polaris, ACE, Sportsman, Ranger and RZR are registered trademarks of Polaris, Inc. Lucas Oil has no endorsement or affiliation with Polaris Inc.